



# QUICK VAC TRANSPORT

## SUCTION UNIT

- HIGH SUCTION OUTPUT
- SMALL AND LIGHT
- **REASONABLE PRICE**
- BATTERY/POWER/CHARGING INDICATORS
- INTEGRATED BED-RAIL HOOK
- **SMART BATTERY MANAGEMENT SYSTEM**

- HIGH SUCTION OUTPUT
- SMALL AND LIGHT
- **REASONABLE PRICE**
- BATTERY/POWER/CHARGING INDICATORS
- INTEGRATED BED-RAIL HOOK
- **SMART BATTERY MANAGEMENT SYSTEM**

## QUICK VAC TRANSPORT

is a compact modern medical device for efficient suction, suitable for home use, surgeries and emergency transport suction. A double piston oil-free vacuum pump guarantees a dynamic suction output (20 l/min) and it's completely maintenance free. By using the suction regulator it's possible to control the vacuum level in the range of 0 – 85 kPa. The value is monitored by a vacuum gauge. The suction unit can be equipped with 0,5 l, 1 l jar, single use jar Flovac 1l or with single use bag Flovac 1l.



## TECHNICAL SPECIFICATIONS

### PARAMETERS

Max. vacuum	85 kPa (637 mmHg) ± 8%
Dimensions (w × h × l)	510 × 230 × 140 mm (incl. 1 l jar)
Weight	5,5 kg
Bottles	0,5 / 1 / FLOVAC 1 / bag FLOVAC 1l
Voltage	90 Vac to 250 Vac 47 Hz to 63 Hz
Suction output	20 l / min *
Overfill protection device	safety valve in jar
Warranty	1 year
Battery operating time	1,5 hours
Charging time	min. 4 hours charging after LOW BAT indicator is on

\* (short-term use 30 min. run, 10 min. pause)

## MICROBIOLOGICAL SUCTION FILTER (MSF)

Microbiological suction filter is an antibacterial, antiviral suction filter. MSF prevents from possible contamination of the environment by bacteria, viruses and from patient-contaminated particles, which may be transferred when using suction devices. You can prevent possible dissemination of contaminated air from the device to surrounding environment by using MSF and simultaneously protect this device against potential oversuction.

Order No.: 271-022-001 (20 pcs/box)

## QUICK VAC TRANSPORT

### SUCTION UNIT

Quick Vac Transport	Order No.: 11-1230
---------------------	--------------------

## OPTIONAL ACCESSORIES

### FOR ALL MODELS

Cable with car connector 12 V
Support ring for 0,5 l, 1 l jars; Flovac 1 l
Jars 0,5 l, 1 l; Flovac 1 l, Flovac bag 1 l
Suction circuit

